

Amendments to the Claims

1. (Currently Amended) A data input/output (I/O) system connected to an address bus and a data bus, comprising:

a first register that stores data from the data bus in response to an access signal supplied from the address bus, wherein the data is transferred from the first register to a memory as an address signal; and

~~a memory that receives the data stored in the first register and inputs and outputs data from and to the data bus using the data as an address signal~~

a second register that stores data generated by the memory in response to the data from the first register.

2. (Original) The data I/O system of claim 1, further comprising an address generation circuit that generates an address signal accessible by the memory and supplies the address signal to one of the memory and the first register.

3. (Canceled)

4. (Currently Amended) The data I/O system of claim ~~[[3]]~~ 1, further comprising a digital-to-analog (D/A) converter that receives data from the second register and converts the data to an analog signal.

5. (Previously Presented) The data I/O system of claim 4, wherein the address generation circuit generates a circulating address signal, and the D/A converter generates an analog signal having a periodic waveform by repetitively receiving data from the second register.

6. (Original) The data I/O system of claim 2, wherein the address generation circuit includes:

a counter that counts clock signal pulses and generates the address signal, which corresponds to the count value;

a control register that stores an end address of the data stored in the memory; and

a comparator connected to the counter and the control register to compare the end address and the address signal and supply a signal for resetting the count value of the counter when the end address and the address signal match.

7. (Original) The data I/O system of claim 6, wherein the counter is an up-and-down counter that performs one of an incremental count operation and a decremental count operation in response to a switching signal, and the up-and-down counter resets the count value in response to a clear signal in the incremental count operation and sets the end address to the initial value in the decremental count operation when the count value has underflowed.

8. (Original) The data I/O system of claim 1, further comprising:
a decoder connected to the address bus to generate a control signal in response to the access signal; and
a switch circuit connected between the memory and the data bus and being conductive in response to the control signal.

9. (Previously Presented) A data I/O system, comprising:
an analog-to-digital (A/D) converter that converts an analog signal to a digital signal;
a memory connected to the A/D converter that stores the digital signal;
a first register connected to the memory that stores an address signal; and
an address generation circuit connected to the first register and including a control register that receives control data from a processing unit, wherein the address generation circuit that generates the address signal and supplies the address signal to the first register.

10. (Original) A data I/O system, comprising:
a first function block including,
a first register that stores a first address signal,
a first memory that receives the first address signal stored in the first register and inputs and outputs data in accordance with the first address signal,

a first address generation circuit that generates the first address signal successively and supplies the first address signal to the first register, and

a digital-to-analog (D/A) converter that receives data from the first memory and converts the data to an analog signal;

a second function block connected to the first function block, including,

an analog-to-digital (A/D) converter that converts the analog signal to a digital signal,

a second memory that stores the digital signal,

a second register connected to the second memory that stores a second address signal, and

a second address generation circuit connected to the second register that generates the second address signal successively and supplies the second address signal to the second register; and

a processor that receives the digital signal from the second memory, corrects the data stored in the first memory, and supplies the corrected data to the first memory.

11. (Currently Amended) A method for inputting and outputting data, comprising the steps of:

storing ~~an address signal~~ data from an address bus in a first register in response to an access signal supplied from the address bus;

~~writing data to a storage device in accordance with the address signal stored in the register;~~

~~storing a circulating address signal in the register; and~~
~~reading data from the storage device in accordance with the circulating address signal~~
~~stored in the register~~

transferring the data from the first register to a memory as an address signal; and
storing data generated by the memory in a second register in response to the
data from the first register.

12. (Currently Amended) A data input/out (I/O) system connected to an address bus and a data bus, comprising:

a first register that stores data from the data bus in response to an access signal supplied from the address bus; and

a memory that receives the data stored in the first register and inputs and outputs memory data from and to the data bus using the data as an address signal; and

a second register that stores data generated by the memory in response to the
data from the first register.

13. (Currently Amended) A microprocessor comprising:

a central processing unit (CPU) connected to an address bus and a data bus;

a first register that stores data from the data bus in response to an access signal supplied from the address bus; and

a memory that receives the data from the first register as an address signal to access memory cells therein and inputs and outputs memory data from and to the data bus; and

a second register that stores data generated by the memory in response to the data from the first register.

14. (Currently Amended) A microprocessor connected to a memory comprising:

a central processing unit (CPU) connected to an address bus and a data bus ~~that~~, in which the central processing unit generates control data;

an address generation circuit that generates a sequence of addresses in response to the control data from the CPU; and

a memory control circuit that accesses the memory in accordance with the sequence of addresses from the address generating circuit; and

a register that stores data generated by the memory in response to the data from the address generating circuit, wherein the control data indicates start and stop of the address generation circuit.

15. (New) A data input/output (I/O) system connected to an address bus and a data bus, comprising:

a first register that stores data from the data bus in response to an access signal supplied from the address bus, wherein the data is transferred from the first register to a memory as an address signal; and

a second register that stores data generated by the memory in response to the data from the first register.

16. (New) A microprocessor comprising:

a CPU connected to an address bus and a data bus;

a first register that stores data from the data bus in response to an access signal supplied from the address bus, wherein the data is transferred from the first register to a memory as an address signal; and

a second register that stores data generated by the memory in response to the data from the first register.